

PRINTING TYPES

- ✓ aqueous
- ✓ latex
- ✓ UV

COLOUR

- ✓ white

ASPECT

- ✓ matt, smooth,
flexible

USE

- ✓ indoor

ENVIRONMENT

- ✓ PVC Free

CERTIFICATION

- ✓ n/a

DESCRIPTION

Non-woven fabric composed with cellulose and polyester fibres bonded by an acrylic. Coated on the front side for digital inkjet printing.

PROPERTIES

Smooth matte aspect.
Very good color rendition.
Very good dimensional stability.
Masks small wall imperfections, wall preparation is simplified.
Good resistance to tearing during installation.
Easy to install.
Can be cleaned with a sponge and soapy water.

APPLICATIONS

Wall covering to be printed or painted.
Non-woven to be glued: use a non-woven wallpaper glue adapted to the surface to be decorated.
Lay edge-to-edge or with overlap.
For further details, see "Tips for printing and cutting strips" below and the installation tip sheet.

INSTRUCTIONS FOR PRINTING AND CUTTING

Laying edge to edge :

- with digital cutting: printing with an overlap of 2 to 4 mm, then cutting this overlap to size.
- with manual cutting: printing with an overlap of 1 cm, then cutting the strips in overlaying flat (double cutting). Laying with overlap :
- printing with an overlap of 1 to 1.5 cm. Laying on the wall and double cut on the wall.

These installation tips are valid for all non-woven fabrics.

Removal instructions :

Remove the printed surface, spray warm water on the remaining part to reactivate the glue and remove the last wet layer. Finally, remove adhesive residues with a damp sponge.

TECHNICAL SPECIFICATIONS

<i>Grammage</i>	170 +/-4%	g/m ²	ISO 536
<i>Thickness</i>	295-325	μm	EN 20534
<i>Main</i>	1,8	cm ³ /g	ISO 534
<i>Moisture</i>	n/a	%	-
<i>Smoothed Beek</i>	n/a	Sec	ISO 537
<i>Tensile resistance strength*</i>			
- <i>machine direction</i>	n/a	N	ISO 1924-2
- <i>cross direction</i>	n/a	N	ISO 1924-2
- <i>in the wet state</i>	n/a	N	DIN ISO3781
<i>Tear resistance strength*</i>	n/a	%	A 10-011/27
<i>Opacity*</i>	n/a	%	ISO 2471
<i>Whiteness</i>	130	%	ISO 11475

* before gluing the reverse side

AQG1011